

Making Security Easier.

## GKB Diplomat<sup>™</sup> 120B IP Camera

Self-Networking Indoor IP Box Camera with Fixed Lens

GKB Diplomat<sup>™</sup> 120B is a professional IP camera for indoor installation and targeting large or tender-based installation projects requiring advanced network technologies. It is also the world's first professional network camera to feature automated self-networking for fast network set-up and installation.

Features:

- Automated Self-Networking GKB Diplomat<sup>™</sup> 120B is a self-networking IP camera that eliminates the need for complicated and time-consuming router configuration. Bundled GKB Envoy<sup>™</sup> software reduces network set-up to less than 30 seconds.
- H.264 Video Compression GKB Diplomat<sup>™</sup> 120B features H.264 video compression for superior video resolution. The low bit-rate of H.264 codec makes for smoother video streaming, even under the most unfavorable of network environments.
- Cloud Platform

Cloud platform framework brings IP solution to a new level. The IP cameras are managed by account and password. The live image and playback can display anytime anywhere via the IE browser, without any extra software installed.

3G Mobile Access

GKB Diplomat<sup>™</sup> 120B enables 3G mobile surveillance by RTSP. Mobile access is simply done by entering account and password. Support iPhone, Windows Mobile, and Symbian.



## Alternate Views

GKB Diplomat <sup>™</sup>	" 120B IP Can	hera
<u></u>		
Video	Image Sensor	CMOS Sensor
	Video Compression	H.264 Base Line
	Video Streams Resolution	8
		640(W) x 480(H)
	Resolution	640x480, 320x240, 160x120
	Frame Rate	Up to 30fps in all resolution
	Min. Illumination	0.1Lux
	Gamma	0.45
	S/N Ratio	50db
	Sync. Mode	Internal Sync.
	Scanning System	Progressive
	Shutter Control	NTSC: 1/60~1/100,000 sec
		PAL: 1/50~1/100,000 sec
	BNC Video Output	N/A
	Night Mode	Auto
	White Balance	AWB
Audio	Audio Input	Built-in microphone
Power	Power Supply	12V DC
	Power Consumption	< 4W
Lens	4mm Board Lens	
Dimension	50 (H) x 50 (W) x 110 (L) mm	
Weight	170g	
Operating Temperature	-20℃ ~ 70℃	
Humidity	20%~90% RHG	
Note	No SD slot	
	1	
Networking	Protocol	HTTP, TCP, UDP, DNS, DHCP, PPPoE, Samba
	Ethernet	10/100Mps Fast Ethernet RJ-45 port
Software	Operating System	Windows XP and above
	Software Package	NVR10:64 Channel NVR Viewer-11
	Software rackage	Remote Playback Setup Software Utility

